

Universal testing machine DI-CP/V4 Pro Series





Technology



The DI-CP/V4 model, which is part of the PRO series, has been designed to perform tensile, compression, bend/flex and shear testing, with nominal capacities between 400 and 2000 kN. Tension is always tested using the hydraulic grips, located in lower area, and compression in the upper test area.

Each machine includes HoyWin[®] test control software, and our custom designed electronics. This enables users to extract maximum performance and precision, through a simple and intuitive interface.

Applications include the testing of metals, cables, fixings, concrete, composites, etc.



Characteristics:

- Double test area.
- HBM[®] load cell (international leader in this technology).
- HoyWin[®] software for material testing in multiple languages.
- 21.5" touch screen.
- Computer integrated in the machine.
- Remote Control Smart|Remote Control.
- Hydraulic tensile grips.

Optional accessories:

- Perimeter guards.
- Large range of tools for each test. Compression, nut testing Bending, shear, etc.
- Grips for shoulder or screw head specimens.
- Extensometers.
- Wedges to fit different specimens.



Capacity kN		400-600	1000	1500-2000
Piston speed *1	Forward	150	150	100
	Backward	200	250	150
Piston travel		500	500	500
Space between grips		100-600	100-600	100-600
Tensile horizontal space		620	805	810
Compression horizontal space		340	450	500
Maximum height		3400	3900	4000
Dimensions	Width Depth	1050	1250	1250
		900	1000	1000
	Height	2900	3400	3500
Weight _{Kg}		3600	5000	6000
Power supply			380-III	

Force transducer

Machine accuracy (Class) *2	0.5
Range	0.4% – 100% FS
Resolution	0.001% FS

Displacement transducer		
Туре	Linear encoder	
Resolution	< 0.01mm	
Accuracy	< 0.1%	

^{*1} Higher speeds and larger sizes available upon request. ^{*2} According to Standards ISO 7500 and ASTM E4.



Year Warranty with all Hoytom[®] machines

Die Maschine

When you purchase a Hoytom® machine the equipment comes with a 3 year warranty.





www.hoytom.com

 \times

hoytom@hoytom.com

